

EFFICIENT 13 SEER AIR CONDITIONER ENVIRONMENTALLY BALANCED R-410A REFRIGERANT

1-1/2 THRU 5 TONS SPLIT SYSTEM

208 / 230 Volt, 1-phase, 60 Hz

REFRIGERATION CIRCUIT

- Scroll compressors on all models
- Filter-drier supplied with every unit for field installation
- External high and low refrigerant service ports
- Copper tube/aluminum fin coil

PERFORMANCE

- 2-speed fan motors factory wired on some models
- Compressor Sound Jacket standard

EASY TO INSTALL AND SERVICE

- Comfort Alert™ Diagnostics device on 18, 36–60 models
- Easy access service valves on all models
- Innovative control box design
- High and low pressure switches
- Fan motor in-line disconnect plug
- Only two screws to access control panel
- Factory charged with R-410A refrigerant

BUILT TO LAST

- High gloss, baked-on powder coat finish over galvanized steel
- Post-painted (black) coil fins
- Coated, weather-resistant cabinet screws
- Coated inlet grille with 3/8" (10mm) spacing for extra protection (hail guard)
- Corner Posts for extra strength and style

LIMITED WARRANTY*

- 1 year No Hassle Replacement™ limited warranty
- 5 year parts limited warranty (including compressor and coil)
 - With timely registration, an additional 5 year parts limited warranty (including compressor and coil)

* For residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.



Use of the AHRI Certified™ Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.



UNIT PERFORMANCE DATA

| Model Number | Size (tons) | Nominal Btu/hr | Min. Circuit Amps | Max. Fuse/Breaker | Operating Dimensions height x width x depth in. (mm) | Ship / Operating Weight lbs. (kg) | Notes |
|--------------|-------------|----------------|-------------------|-------------------|--|-----------------------------------|-------|
| C4A318GKF | 1½ | 18,000 | 11.8 | 20 | 25-5/16 x 23-1/8 x 23-1/8 (643 x 587 x 587) | 143 / 117 (65 / 53) | |
| C4A324GKF | 2 | 24,000 | 17.6 | 25 | 28-11/16 x 31-3/16 x 31-3/16 (729 x 793 x 793) | 213 / 176 (97 / 80) | |
| C4A330GKF | 2½ | 30,000 | 16.8 | 25 | 32-1/8 x 31-3/16 x 31-3/16 (816 x 793 x 793) | 199 / 165 (90 / 75) | |
| C4A336GKN | 3 | 36,000 | 21.9 | 35 | 25-5/16 x 31-3/16 x 31-3/16 (643 x 793 x 793) | 196 / 160 (89 / 73) | |
| C4A342GKN | 3½ | 42,000 | 23.5 | 40 | 32-1/8 x 31-3/16 x 31-3/16 (816 x 793 x 793) | 230 / 195 (104 / 89) | |
| C4A348GKN | 4 | 48,000 | 26.0 | 40 | 35-1/2 x 31-3/16 x 31-3/16 (902 x 793 x 793) | 243 / 203 (110 / 92) | |
| C4A360GKN | 5 | 60,000 | 34.2 | 50 | 28-11/16 x 31-3/16 x 31-3/16 (729 x 793 x 793) | 250 / 215 (113 / 98) | |