

## UP TO 16 SEER SINGLE STAGE COMMUNICATING AIR CONDITIONER

1½ THRU 5 TONS SPLIT SYSTEM  
208 / 230 Volt, 1-phase, 60 Hz

### REFRIGERATION CIRCUIT

- Scroll compressors on all models
- Filter-drier supplied with every unit for field installation
- External high and low refrigerant service ports
- Copper tube/aluminum fin coil

### PERFORMANCE

- Communicating, self-configuring operation ION™ Wall Controls
- Outdoor temperature sensor factory installed
- Compressor sound blanket standard
- Isolation compressor grommets

### EASY TO INSTALL AND SERVICE

- Text based diagnostics with ION™ wall controls
- Easy Access service valves on all models
- Innovative control box design
- High and low pressure switches
- Fan motor in-line disconnect plug
- Only two screws to access control panel
- Factory charged with R-410A refrigerant


### BUILT TO LAST

- High gloss, baked-on powder coat finish over galvanized steel
- Post-painted (black) coil fins
- Coated, weather-resistant cabinet screws
- Coated inlet grille with 3/8" (10mm) spacing for extra protection
- Corner posts for extra strength and style

### WARRANTY\*

- 5 year No Hassle Replacement™ limited warranty
- 5 year parts limited warranty (including compressor and coil)
  - With timely registration, an additional 5 year parts limited warranty (including compressor and coil)

\* For residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.



Use of the AHRI Certified™ Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to [www.ahridirectory.org](http://www.ahridirectory.org).

UNIT PERFORMANCE DATA							
Model Number	Size (tons)	Nominal Btu/hr	Min. Circuit Ampacity	Max. Fuse or Breaker	Operating Dimensions height x width x depth in. (mm)	Ship / Operating Weight lbs. (kg)	Notes
CSA618GKA	1½	18,000	11.8	20	"28-11/16 x 31-3/16 x 31-3/16 (729 x 792 x 792) "	213 / 176 (96 / 80)	
CSA624GKA	2	24,000	17.6	25	"28-11/16 x 31-3/16 x 31-3/16 (729 x 792 x 792) "	212 / 176 (96 / 80)	
CSA630GKA	2½	30,000	16.7	25	"32-1/8 x 31-3/16 x 31-3/16 (816 x 792 x 792) "	223 / 187 (101 / 85)	
CSA636GKA	3	36,000	18.2	30	"30-1/16 x 35 x 35 (764 x 889 x 889) "	243 / 200 (110 / 91)	
CSA642GKA	3½	42,000	23.4	40	"40-1/4 x 35 x 35 (1023 x 889 x 889) "	297 / 253 (135 / 115)	
CSA648GKA	4	48,000	26.1	40	"40-14 x 35 x 35 (1023 x 889 x 889) "	340 / 295 (155 / 114)	
CSA660GKA	5	60,000	28	40	"47-1/16 x 35 x 35 (1196 x 889 x 889) "	374 / 327 (169 / 148)	